

THE LEADING EDGE IN FIRE & SMOKE CONTROL SYSTEMS

>FC240, THE FOUR HOUR FIRE CURTAIN

BLE Smoke & Fire Curtains recognised early on that integrity requirements would increase in line with modern building products.

This led to the early design of the 240-minute fire integrity curtain.

In line with BLE Smoke & Fire Curtains considerable investment in global testing, the FC series was put through its paces with various testing facilities.

The result was a fully certified 240-minute integrity curtain retaining all the advantages of the BLE system; excellent build quality, simple design, backward compatibility and many control and interface options.



- EN 1634-1 FR & Integrity 240 minutes
- EN 1634-3 Air Leakage to Head & Jamb
- BS 476 Part 22 FR & Integrity Testing 270 mins
- UL10D Fire Protective Curtains 120 mins
- UL10D S With Smoke Sealing
- UL864 Releasing Devices
- AS 1530.4 FR & Integrity test 120 mins
- FRT12 Macau FR & Integrity 240 mins

BLE Smoke & Fire Curtains are the only company to have achieved a UL Listing for products of this class.

- Fabric Type c41000wk
- Fabric Rating 240minutes
- Fabric Weight 700g/ sq metre
- Curtain Descent Gravity Fail Safe

BLE Smoke & Fire Curtains also have a large number of assessments on their tests based around customers' specific requirements for individual projects.

